



ABC Dry Powder is a multi-purpose, and truly versatile extinguishant suitable for Class A, B, C & Electrical fires. Our range of Fire Extinguishers are manufactured under our stringent Quality Management System to ISO 9001.

FEATURES

- Available in a wide range of sizes and tested to remarkably high performance fire-ratings in accordance to BS EN3-7, and Singapore Standards SS EN3 : 2012.
- The cylinders are of steel construction, coated with epoxy powder for high corrosion resistance, and fitted with brass valves with pressure gauges.
- Colour Coded for instant recognition
- Effective operation at both high and low temperature
- Ideal for Industrial, Commercial and Domestic environment



| Model No. | ABC-EN3-1K | ABC-EN3-2K | ABC-EN3-4K | ABC-EN3-6K | ABC-EN3-9K |
|-------------------|---|---------------|----------------|----------------|----------------|
| Capacity | 1.0 kg | 2.0 kg | 4.0 kg | 6.0 kg | 9.0 kg |
| Approx. Gross Wt. | 2.0 kg | 3.3 kg | 7.1 kg | 9.1 kg | 12.8 kg |
| Discharge Time | 6 – 10 secs | 8 – 12 secs | 11 – 15 secs | 17 – 21 secs | 20 – 24 secs |
| Throw Range | 4 m | 4 m | 5 m | 5 m | 5 m |
| Fire Rating | 5A / 21B / C | 13A / 55B / C | 21A / 113B / C | 27A / 144B / C | 34A / 233B / C |
| Diameter x Height | Ø86x 335mm | Ø111 x 365mm | Ø138 x 447mm | Ø161 x 515mm | Ø185 x 540mm |
| Working Pressure | 12 bar | 14 bar | | | |
| Test Pressure | 30 bar | | | | |
| Propellant | Nitrogen (N ₂) | | | | |
| Temp. Range | Operational between -20°C to +60°C | | | | |
| Finishing | Red – Epoxy Powder Coated | | | | |
| Standard | Designed & Manufactured to BS-EN 3-7 and Singapore Standards SS EN3 :2012 | | | | |

Multron Systems Pte Ltd

217 Kallang Bahru, Multron Building, Singapore

6395 6868

info@multron.com

6395 6869

www.multron.com

