



Foam Trolley Fire Extinguishers are especially suitable for flammable liquids. This range offers a combination of fire performance with ease of service as the trolley unit can be maneuvered and operated by one person, and suitable for areas with high risk fire such as industrial facilities.

The cylinders are deep drawn from cold rolled steel with hot forged brass operating valve fitted with pressure indicator. Coated with epoxy powder, the cylinder offers high corrosion resistance.



**Foam Trolley
Fire Extinguisher**

Model	EXT-FOM-25K	EXT-FOM-40K	EXT-FOM-65K	EXT-FOM-90K
Filled Weight	25 kg	40 kg	65 kg	90 kg
Volume of Cylinder	35.6 Litre	60 Litre	90 Litre	125 Litre
Discharge Time	≥ 65 sec	≥ 120 sec	≥ 150 sec	≥ 180 sec
Distance of Throw	≥ 9m			
Fire Rating	6A 12B	13A 18B	21A 24B	27A 35B
Operating Temperature	5°C to 55°C			
Extinguishing Agent	3% AFFF Foam Solution			
Packing Size (cm)	47 x 51 x 99	55 x 50 x 100	57 x 57 x 118	60 x 60 x 120

Multron Systems Pte Ltd

217 Kallang Bahru, Multron Building, Singapore 339 347

☎ 6395 6868
📠 6395 6869

✉ info @ multron.com
🌐 www. multron. com

