



The **MULTRON** Modular Automatic Fire Extinguisher using ABC Dry Powder offers a simple and cost effective stand-alone unit for Fire Protection. It is activated by means of a heat sensitive built-in Bulb with the Valve.

Once the ambient temperature reaches the Bulb's rated temperature, it will burst to open the valve and release the fire extinguishing agent into the protected area.

- Ceiling-Mounted to save storage space
- Discharge Valves are complete with Pressure Gauge and Activation Bulb (Standard Rating at 68 deg. C)
- Optional Pressure Switch may be added to monitor any discharged condition. (To be specified when ordering)



CEILING MOUNT MODULAR AUTOMATIC FIRE EXTINGUISHER

MODEL	EXT-MKX-4K	EXT-MKX-6K	EXT-MKX-12K
Cylinder Diameter	Ø 180 mm	Ø 213 mm	Ø 302 mm
Cylinder Height (without Mounting Bracket)	260 mm	285 mm	268mm
Volume	5.5 Litres	8.5 Litres	13.9 Litres
Approx. Tare Weight	2.2 kg	4.2 kg	7.5 kg
Filled Weight	4.5 kg	6 kg	12 kg
Approx. Gross Weight	6.7 kg	10.2 kg	19.5 kg
Working Pressure	15 bar		
Test Pressure	25 bar		
Temperature Range	-20°C to 60°C		
Maximum Coverage Area at 3m Height	4.5 sq. m	6 sq. m	12 sq. m

Multron Systems Pte Ltd

217 Kallang Bahru, Multron Building, Singapore 339 347

6395 6868
6395 6869

info @ multron.com
www. multron. com

