



## PRESSURE REDUCING VALVE

- PRV-HR63-25
- PRV-HR63-50

The PRV-HR63-25 and PRV- HR63-50 Pressure Reducing Valves are suitable to be used in the Water Supply Line of Hosereel Systems for Fire Protection.

Available in two commonly used sizes of Ø2" and Ø1", these Valves could effectively reduce the Inlet of the Hosereel to the designed Nominal Working Pressure.

Please note that these Valves are to be installed by qualified Technicians and field adjusted to meet each individual site requirement.



Model : HR63-50



Model : HR63-25

Technical Information	Model PRV-HR63-50	Model PRV-HR63-25
Inlet / Outlet Connection	Female Ø2" BSP	Female Ø1" BSP
Body Material	Brass	Brass
Max. Inlet Pressure	Up to 20 bar (290 PSI)	
Recommended Outlet Pressure	Between 1 to 4 bar (14.5 to 58 PSI)	

Another Quality Product by :-



Multron Systems Pte Ltd  
217 Kallang Bahru, Multron Building  
Singapore 339 347

+65 6395 6868



Info@multron.com

+65 6395 6869

### DATA SHEET

Copyright © The information contained in this Data Sheets remains the property of Multron Systems Pte Ltd, and is not to be altered or reproduced without permission.

Multron reserves the right to change any specification without prior notice.

Version : 10-9-2021