A1 FIRE® Portable Fire Extinguisher

CO2 FIRE EXTINGUISHERS

Suitable for Class B risks involving flammable liquids such as such as oils, grease, gasoline, paint and etc.



Model No.	A1-C2	A1-C5
Capacity	2.0 kg	5.0 kg
Weight	6.2 kg	13.7 kg
Fire Rating	21B	70B
Diameter x Height	Ø104x 600mm	Ø136 x 760mm
Working Pressure	55 Bar	
Test Pressure	250 Bar	
Propellant	Carbon Dioxide (CO2)	
Temp. Range	Operational between –30°C to +60°C	
Finishing	Red – Epoxy Powder Coated	
Mounting	Wall bracket included	
Standard	Singapore Standards SS EN3-7:2012, SS EN3-9:2012	

FOAM FIRE EXTINGUISHERS

Ideal where both A & B class fire risk exists. Foam is particularly suited to class B fires caused by materials such as gasoline, oils, grease, paint and etc.



Model No.	A1-F9
Capacity	9.0 Litres
Weight	13.6 kg
Fire Rating	21A / 183B
Diameter x Height	Ø184x 620mm
Working Pressure	12 Bar
Test Pressure	25 Bar
Propellant	Nitrogen (N2)
Temp. Range	Operational between 5°C to +60°C
Finishing	Red – Epoxy Powder Coated
Mounting	Wall bracket included
Standard	Singapore Standards SS EN3-7:2012, SS EN3-8:2023

WATER FIRE EXTINGUISHERS

Suitable for Class A fires caused by the combustion of solid materials, such as wood, paper, cloth, plastic and etc.



Model No.	A1-W9
Capacity	9.0 Litres
Weight	13.6 kg
Fire Rating	21A
Diameter x Height	Ø184x 620mm
Working Pressure	12 Bar
Test Pressure	25 Bar
Propellant	Nitrogen (N2)
Temp. Range	Operational between 5°C to +60°C
Finishing	Red – Epoxy Powder Coated
Mounting	Wall bracket included
Standard	Singapore Standards SS EN3-7:2012, SS EN3-8:2023

Quality Products Distributed By:-

Multron Systems Pte Ltd
217 Kallang Bahru, Multron Building, Singapore 339 347
6395 6868 info@multron.com
6395 6869 www.multron.com

Due to constant improvement in our products, we reserved the right to modify or withdraw any product or service without prior notice.

Version : 22-10-2026